



GORLITZ SEWER & DRAIN INC.



A WORD TO OUR CUSTOMERS



Since 1980, Gorlitz Sewer & Drain, Inc is one of the United States leading manufacturers of quality sewer and drain cleaning machines and accessories. Committed to excellence, Gorlitz has both the personnel and facilities to assure unequalled service and dependability. With an emphasis on customer service and satisfaction, Gorlitz Sewer & Drain, Inc. is ready to give you all the assistance you need.

GORLITZ EQUIPMENT

Gorlitz electric sewer & drain cleaning machines and high pressure water jetters are built with the highest quality materials and components available. All parts are die cut for accurate repeatability and precision machined to close tolerances to insure a proper fit. Frames are built from high tensile steel tubing to add strength and reduce weight. Their low profile design ensures greater stability and safety. All frames are zinc plated, painted or powder coated to ensure protection against corrosion.

HIGH EFFICIENCY ELECTRIC MOTORS

Electric models are equipped with high efficiency, continuous duty, ball bearing motors. In addition, these motors are equipped with capacitors, overload protection or manual reset button. Our motors operate on 110 volt, 60 cycle single phase. Motors with different voltage are available and can be furnished upon special request.

DEPENDABLE GASOLINE ENGINES

Gasoline powered jetters are equipped with dependable four-stroke KOHLER or HONDA engines. Some of the many standard features of these virtually trouble free engines are a maintenance free electronic ignition, overhead valves to reduce oil and fuel consumption and automatic decompression for easy starting. These engines are recognized for their excellent quality, reliable performance and nationwide support facilities.

HIGH PRESSURE WATER PUMPS

Our pumps were selected due to their advanced design, superior quality, proven continuous heavy-duty performance and long life expectancy. The exterior pump section is cast from solid bronze and all internal hardware is fabricated from stainless steel. The ceramic plungers provide a durable wear surface and resistance to abrasion for maximum seal life. The preset seals require no adjustments.

CABLE FITTINGS AND CONNECTORS

Gorlitz offers several styles of cable fittings to give the operator versatility and adaptability. Our cable splices, cable ends and connectors are non-weld fittings that have been machined with a tapered start for easy installation. For extra strength and security, the fittings may be tack welded to the sewer cable. Gorlitz fittings are offered with a standard allen head cap screw or split pin lock.

OPEN REEL OR ENCLOSED DRUM CONSTRUCTION

Most sewer cleaning machines are offered with an open reel or enclosed drum construction. The many advantages of models equipped with open reels include easy accessibility, visibility, a reduction in corrosion and therefore a longer cable life span. Models supplied with enclosed polyethylene or aluminum drums are a matter of operators choice. They provide additional safety and are recommended if the work is being performed next to walls or inside buildings.

PLUMBER SNAKE GO 68HD


RJM

360-828-5732

The Gorlitz Model GO 68HD heavy duty drain cleaning machine without compromise, is the choice of the professional. Due to its power, motor and gearbox combination this model will out-perform and out-last all other machines in its class.



GO 68HD



GO 68HDPE

This heavy duty model is equipped with a 3/4 HP reversible motor and separate 10:1 ratio gearbox. Additional features include skid bars for added frame protection, large rubber wheels and a front handle for easy transportation. The rear rubber bumpers absorb shock when positioning the machine on its back while the added feature of a tow ring helps to pull the machine up the ramp. This model performs smoothly, quietly, efficiently and is designed for easy one-man operation. Model GO 68HD is perfect for clearing roots, sludge, grease, sand and rags in sewer lines from 3" to 10" in diameter up to 500 feet long.

The Plumber Snake GO 68HD is available in two different versions, either with an open steel reel or enclosed polyethylene drum.

ACCESSORIES

Knife Assortment	11/16" X 150' Cable
Cable Connectors	Allen Wrenches
Regular Chucks	For/Rev Switch
Cable Splices	Metal Toolbox
Cone Chuck	Foot Switch
Retriever	GFCI

SPECIFICATIONS

3/4 HP Ball Bearing Motor
10:1 Ratio Heavy Duty Gearbox
Cable Rotation: 175 RPM
Pipe Size: 3" to 10" Diameter.
Maximum Pipe Length: 500 Feet
Dimensions: 43" L x 26" W x 30" H
Net Weight: 248 LBS (Drum)
Net Weight: 255 LBS (Reel)

Both plumber snakes are shown with our optional Gorlitz PowerCable Feeder and Puller # T 01 and Mounting Bracket #T02. It is recommended to operate this drain cleaning machine with our cable feeder and puller for safer and more efficient pipe cleaning procedure. The use of the feeder also avoids operator stress and fatigue.



MODEL GO 68 SERIES

Gorlitz Plumber Snake GO 68 is an outstanding model due to its power, straight forward construction and simplicity in operation. This model will open tough stoppages and should satisfy the most experienced operator.

The Gorlitz Plumber Snake GO 68 frame is durable and simply constructed. Powered by a 1/2 HP ball bearing reversible geared motor, this model operates almost noiselessly. Extra additions include skid bars for frame protection, large wheels, tow ring, front and rear handles for added ease of transportation, loading or unloading of machine. This model cuts through roots, grease, rags and other foreign objects in sewer lines from 3" to 8" in diameter over 300 feet long.

Model GO 68 is available with either an open steel reel or enclosed polyethylene drum.

ACCESSORIES

Knife Assortment	11/16" X 150' Cable
Cable Connectors	Allen Wrenches
Regular Chucks	For/Rev Switch
Cable Splices	Belt Tensioner
Cone Chuck	Metal Toolbox
Retriever	Foot Switch
GFCI	



GO 68



GO 68 PE

Both plumber snakes are shown with our optional Gorlitz Power Cable Feeder and Puller # T 01 and Mounting Bracket # T 02. It is recommended to operate this drain cleaning machine with our cable feeder and puller for safer and more efficient pipe cleaning procedure. The use of the feeder also avoids operator stress and fatigue.

SPECIFICATIONS

1/2 HP Geared Motor
Cable Rotation: 160 RPM
Pipe Size: 3" to 8" Diameter.
Maximum Pipe Length: 300 Feet
Dimensions: 43" L x 26" W x 30" H
Net Weight: 231 LBS (Drum)
Net Weight: 238 LBS (Reel)


MODEL GO 62 SERIES

Reduced in size but powerful in its application, this combination machine was designed to fill the gap between our larger sewer and smaller sink cleaning machines. Because of its power and versatility it is also very popular with the general contractors and professional plumbers.

The Gorlitz Model 62 is a mirror image of our larger Model GO 68. Extremely versatile and being one of our most demanding combination machines, the Model GO 62 is highly preferred due to its smaller size and lighter weight. Easy to transport to the job site, the GO 62 includes an assortment of three interchangeable reels or drums that can handle most any cleaning job. The ball bearing 1/4 HP reversible steel geared motor develops approximately 100 lbs. of torque and cleans sewer and drain lines from 1 1/2" to 4" in diameter up to 200 feet long.



GO 62A



GO 62A PE

SPECIFICATIONS

1/4 HP Geared Motor
Cable Rotation: 165 RPM
Pipe Size: 1 1/2" to 4" Diameter.
Maximum Pipe Length: 200 Feet
Dimensions: 35" L x 22" W x 24" H
Net Weight: 146 LBS (Drum)
Net Weight: 153 LBS (Reel)

ACCESSORIES

GO 62A Accessories Listed

Knife Assortment 5/8" x 100' Cable
Cable Connectors Allen Wrenches
Regular Chuck For/Rev Switch
Cable Splices Belt Tensioner
Cable Ends Metal Toolbox
Retriever Foot Switch
GFCI

	GO 62A	GO 62	GO 62A PE	GO 62 PE
621 5/8" REEL	•	•		
501 1/2" REEL		•		
502 3/8" REEL		•		
621 P 5/8" DRUM			•	•
501 P 1/2" DRUM				•
502 P 3/8" DRUM				•
5/8" x 100' CABLE	•	•	•	•
3/8" x 90' CABLE		•		•
1/2" x 80' CABLE		•		•

The Model GO 62 Series is available in a variety of reel and/or drum combinations and are completely interchangeable to fully accommodate the needs of the operator. This model does accept our Gorlitz Power Cable Feeder and Puller # T 01 and Mounting Bracket # T 02.

MODEL GO 50 SERIES

Gorlitz Model GO 50 Series is our junior sized machine. Due to its size and portability, this unit is ideally suited to operate in confined areas.

The GO 50 is small, compact and extremely durable. A comfortable rear handle, phenolic wheels and pull stick ease handling or transportation. Equipped with a 1/3 HP capacitor reversible ball bearing motor, this machine cleans drain lines from 1 1/2" to 3" in diameter up to 100 feet long.

ACCESSORIES

GO 50 Accessories Listed

Knife Assortment	1/2" x 80' Cable
Allen Wrenches	For/Rev Switch
Cable Splices	Pull Handle
Cable Ends	GFCI

	GO 50	GO 50A	GO 50B	GO 50 PE	GO 50A PE	GO 50B PE
501 1/2" REEL	•					
502 3/8" REEL		•	•			
501 P 1/2" DRUM			•			
502 P 3/8" DRUM				•	•	
1/2" x 80' CABLE	•		•			
3/8" x 90' CABLE		•		•		
13/32" x 75' CABLE		•				•



GO 50



GO 50A



GO 50 PE



GO 50A PE



Shown with # T 01



Shown with # T 01A

The Model GO 50 Series is available with three different cable sizes and in several reel and/or drum combinations. In addition, the frame is provided with mounting holes to accept any of our optional Gorlitz Power Cable Feeder and Pullers.

SPECIFICATIONS

1/3 HP Ball Bearing Motor	
Cable Rotation: 190 RPM	
Pipe Size: 1 1/2" to 3" Diameter.	
Maximum Pipe Length: 100 Feet	
Storage Dim: 28" L x 18" W x 21" H	
Extended Dim: 40" L x 18" W x 21" H	
Net Weight: GO 50	90 LBS
Net Weight: GO 50 PE	86 LBS
Net Weight: GO 50A	76 LBS
Net Weight: GO 50A PE	71 LBS

Model GO 250 is equipped with a flexible trunk that helps guide the cable into any tub, shower or sink trap. An optional trunk is also available for our GO 380 models to guide the 3/8" diameter cable.

The Gorlitz Models 380/250 Series machine is built with a unique frame construction that ensures durability and strength. The cover is provided with an easily accessible ground fault circuit interrupter, receptacle, on/off and forward/reverse switches. The drums have been equipped with inner hubs to prevent the kinking of cables. These units are driven by a specially designed high torque capacitor start ball bearing motor for clearing sink and drain lines from 1 1/2" to 2" in diameter. Models GO 380/250 Series are available in five versatile cable and drum combinations.



GO 250

ACCESSORIES

GO 380 accessories listed

Knife Assortment	3/8" x 65' Cable
Allen Wrenches	For/Rev Switch
Cable Splices	GFCI
Cable Ends	

	GO 250	GO 380	GO 380A	GO 380/250	GO 380A/250
#382 1 1/2" W DRUM	•			•	•
#381 3" W DRUM		•		•	
#383 3 1/2" W DRUM			•		•
1/4" x 50' CABLE	•			•	•
3/8" x 65' CABLE		•		•	
3/8" x 90' CABLE			•		•



GO 380

SPECIFICATIONS

1/4 HP Ball Bearing Motor
 Cable Rotation: 230 RPM
 Pipe Size: 1 1/2" to 3" Diameter.
 Maximum Pipe Length: 90 Feet
 Dimensions: 18" L x 14" W x 16" H
 Net Weight: 49 LBS

This hand carried machine has remained one of the most popular models due to its compactness and portability. It can be equipped with different drums and cable sizes to accommodate any operators needs.

MODEL GO 15

GO 15



GO 15 SE



SPECIFICATIONS

1/6 HP Ball Bearing Motor

Cable Rotation: 265 RPM

Pipe Size: 1 1/4" to 2" Diameter.

Maximum Pipe Length: 50 Feet

Dimensions: 16" L x 10" W x 14" H

Net Weight: 28 LBS

Small in size and light on weight, smooth and quiet in operation, tough and durable in construction, this model is recommended to clean any kitchen or shower drain effectively.

Gorlitz Model GO 15, with a total weight of only 28 lbs., is our smallest sink cleaning machine. A totally enclosed aluminum drum equipped with a specially designed inner cone and distributor arm reduces the possibility of cables escaping and kinking. The GO 15 contains a specially built high torque capacitor start reversible motor. The 265 rpm cable rotation provides better and faster cleaning of sink lines from 1 1/4" to 2" in diameter up to 50 feet long. This model is also equipped with a flexible trunk to assist the operator in guiding the cable into any drain opening.

ACCESSORIES

Allen Wrenches
For/Rev Switch

1/4" x 35' Cable
GFCI

The Gorlitz Model GO 15 is shown complete with protective rubber feet and watertight neoprene rubber drum sleeve. This machine is attractively powder-coated in red, black or blue.

MODEL GO 31




Gorlitz Model GO 31, the "Handygum", is our only hand held sink and drain cleaning machine. Conveniently constructed with a pistol grip, keyless chuck, and trigger action, the 1.60 amp, 120V reversible motor has a variable speed control from 0-450 RPM's to quickly open clogged drains. Enclosed in an aluminum drum holding up to 50 feet of 5/16" cable, this machine cleans drain lines from 1 1/4" to 2" in diameter up to 50 feet long. Our "Handygum" is also available as a cordless model No. GO 31A.

The Gorlitz Model GO 31 is lightweight (13 lbs), easy to use and comes furnished with a standard 5/16" x 25" right-hand wound cable.


POWER CABLE FEEDER

Gorlitz's heavy duty power cable feeders and pullers T 01 & T 01A is recommended to be installed on all of our sewer & drain cleaning models. Our feeder incorporates various improvements in power, speed and construction. The drive pins, U-brackets, spring pressure pad and heavy duty knob assembly spindle and plate are heat-treated for extended life and longer wear. Most important, all aluminum housings are provided with grease fittings to lubricate the pistons. Our power feeders will advance or retract left or right hand coiled cables from 3/8" to 3/4" in diameter at a rate from 0 to 32 feet per minute depending on machine revolution.

**T 01****T 01A**

REELS

Gorlitz open reels are designed with an inner cone and zerk fitting for shaft lubrication. The fixed inner cone prevents the cable from closing in towards the center of the reel. Because of the open reel construction, the cable tends to last longer as there is little corrosion. In addition, the cable is visible for periodic inspection of wear and tear, and occasional cleaning or lubrication. Our reels may be added or changed at any time to maximize the cleaning capacity of our equipment. If the operation is close to a wall or inside a house, we recommend our canvas splash guards.



- | | | |
|--------------|---------------|---------------------------|
| # 501 GO 50 | Capacity 100' | |
| # 501A GO 50 | Capacity 125' | |
| # 502 GO 50A | Capacity 90' | # 621 GO 62 Capacity 100' |
| # 502 GO 50B | Capacity 75' | # 681 GO 68 Capacity 150' |

Reel Connector

503 3/8" thru 1/2" Diameter



DRUMS

Gorlitz drums are offered in a variety of metals and styles. Drums 381 thru 383 are made of steel and provided with an independent rotating removable inner hub. Drums 681 P, 621 P, 501 P and 502 P are constructed of high density polyethylene and equipped with a fixed inner cone and removable front disc*. The removable hub and fixed cone also prevent the cable from closing-in towards the center of the drums. The steel drums are lightweight, spun for concentricity and almost splash proof.

* Front disc not shown.

Drum connectors:

514 3/8", 13/32", 1/2" Cables


632 5/8" Cable

710 11/16" Cable

711 3/4" Cable



- | | | | |
|---------------|--------------|----------------|---------------|
| # 381 GO 380 | Capacity 65' | # 501 P GO 50 | Capacity 100' |
| # 382 GO 250 | Capacity 50' | # 502 P GO 50A | Capacity 100' |
| # 383 GO 380A | Capacity 90' | # 502 P GO 50B | Capacity 100' |
| | | # 621 P GO 62 | Capacity 100' |
| | | # 681 P GO 68 | Capacity 150' |



CABLES

Standard cables (left-hand coiled) are our most popular cables used for general purpose cleaning. Shown with optional E 01 cable end.



Inner core cables (left or right-hand coiled) are used for heavy duty jobs. When under pressure or torque, the outer coil tightens around the inner core, stiffening the entire cable.



Downhead cables (left or right-hand coiled) feature a downhead to help negotiate turns and bends in pipe lines.



Bulbhead cables up to 13/32" in diameter (left or right hand coiled) have flexible, large diameter open coiled ends that follow the turns of sewer lines with ease and efficiency.



Bulbhead cables from 3/8" in diameter (left-hand coiled) add flexibility and with installed plug and knife allow you to cut through the toughest obstructions.



CABLE DIAMETER AND LENGTH	STANDARD CABLES LEFT HAND	STANDARD CABLES DOWNHEAD	STANDARD CABLES LEFT HAND BULBHEAD	INNERCORE CABLES LEFT HAND	INNERCORE CABLES DOWNHEAD	INNERCORE CABLES LEFT HAND BULBHEAD	STANDARD ANCHOR CABLES LEFT HAND	INNERCORE ANCHOR CABLES LEFT HAND	HANDGUN CABLES RIGHT HAND	HANDGUN CABLES DOWNHEAD	HANDGUN CABLES RIGHT HAND BULBHEAD
1/4 X 35	C 01	DHC 01	CB 01	IC 01	IDHC 01	ICB 01		GC 01	GCD 01	GCB 01	
1/4 X 50	C 02	DHC 02	CB 02	IC 02	IDHC 02	ICB 02		GC 02	GCD 02	GCB 02	
9/32 X 35	C 03	DHC 03	CB 03	IC 03	IDHC 03	ICB 03		GC 03	GCD 03	GCB 03	
9/32 X 50	C 04	DHC 04	CB 04	IC 04	IDHC 04	ICB 04		GC 04	GCD 04	GCB 04	
5/16 X 25								GC 05	GCD 05	GCB 05	
5/16 X 35								GC 06	GCD 06	GCB 06	
5/16 X 50								GC 07	GCD 07	GCB 07	
3/8 X 65	C 05	DHC 05	CB 05	IC 05	IDHC 05	ICB 05					
3/8 X 90	C 06	DHC 06	CB 06	IC 06	IDHC 06	ICB 06					
13/32 X 75	C 07		CB 07	IC 07		ICB 07					
13/32 X 100	C 08		CB 08	IC 08		ICB 08					
1/2 X 80	C 09	DHC 09		IC 09	IDHC 09						
1/2 X 100	C 10	DHC 10		IC 10	IDHC 10						
5/8 X 10							SAC 01	IAC 01			
5/8 X 75	C 11			IC 11							
5/8 X 100	C 12			IC 12							
11/16 X 10							SAC 02	IAC 02			
11/16 X 50	C 13			IC 13							
11/16 X 75	C 14			IC 14							
11/16 X 100	C 15			IC 15							
11/16 X 120	C 16			IC 16							
11/16 X 150	C 17			IC 17							
3/4 X 10							SAC 03	IAC 03			
3/4 X 50	C 18			IC 18							
3/4 X 100	C 19			IC 19							
3/4 X 110	C 20			IC 20							
3/4 X 150	C 21			IC 21							

OTHER CABLE DIAMETERS AND LENGTHS AVAILABLE, PLEASE INQUIRE

Gorlizt cables are made of the finest hard drawn, heat-treated, high tensile strength music wire. Very tough but providing the greatest amount of flexibility and improved fatigue life, each cable is manufactured using our stress relieving process that sets the coils to retain their tension. This new and superior process stabilizes the molecular structure of the coils and therefore ensures higher quality, longer life and less kinking and breaking. We offer different types of left-hand or right hand coiled cables including hollow core or inner core, with downlead or bulbhead attachments. All standard cables 1/4" - 5/16" in diameter are not available with cable ends, while 3/8" - 1/2" in diameter cables have optional cable ends. Standard cables 5/8" - 3/4" in diameter include cable connectors.

STANDARD CONNECTORS



E 01 3/8"
 E 02 13/32"
 E 03 1/2"
 E 04 11/16"
 E 04A 5/8"
 E 04B 3/4"

Gorlitz's cable end fittings E 01 thru E 03 with 1/4" diameter male threaded stud uses blades K 01 thru K 05. Cable end E 04 thru E 04B with 3/8" diameter male threaded stud is designed to be used with blades K 06 thru K 14.



E 05 5/8"
 E 06 11/16"
 E 07 3/4"

Gorlitz's standard slip joint cable connectors are used with all 5/8" thru 3/4" diameter cables.



E 08

Gorlitz's regular chuck is versatile and accepts all blades K 06 thru K 14.



E 08RR

Gorlitz's hex chuck is versatile and accepts all blades K 06 thru K 14.



E 20

Gorlitz's chuck assembly E 20 is a unique combination of our E 08 and E 60 fittings. This special chuck accepts all 3/4" wide blades K 06 thru K 14.



E 21

Gorlitz's chuck assembly E 21 is a combination chuck consisting of our E 08 and E 62 fittings. This chuck accepts all 1" wide blades K 26 thru K 29.



E 09 Accepts
2 Blades
 E 09A Accepts
3 Blades

Gorlitz's heavy duty cone chuck is used on all 4" and larger diameter sewer lines. The outer cone is made of cast bronze and has recessed pockets that lock knives in position. This chuck accepts all single 3/4" wide knives K 19 thru K 22.



E 10

Gorlitz's E 10 slip joint flexible finger leader is specially designed to guide cables easily thru difficult bends in the sewer line. Blades K 06 thru K 14 can be utilized, depending on operators choice.



E 10A

Gorlitz's E 10A flexible finger leader is specially designed to guide 3/8" and 1/2" cables easily thru difficult bends in the drain line.



E 75

Gorlitz's E 75 split pin flexible finger leader is specially designed to guide cables easily thru difficult bends in the sewer line. Blades K 06 thru K 14 can be utilized, depending on operators choice.



E 11 10-24

Gorlitz's allen head cap screw is used on all slip joint connectors and chucks.



E 12 5/32"
 E 13 1/8"
 E 14 3/32"

Gorlitz's allen wrench E 12 is used on all our allen screws. Wrenches E 13 and E 14 are replacement wrenches for our tool kits. All wrenches are also available in a 9" long T-handle style.



E 12A 5/32"
 E 13A 1/8"
 E 14A 3/32"

STANDARD CONNECTORS



E 15 11/16"
E 15A 3/8"
E 15B 1/2"
E 15D 3/4"

Gorlitz's female coupler E 15 is a specialty item which attaches to our E 09 and E 09A 1/2" diameter threaded stud to accept an optional whip attachment. Part E 15A and E 15B are provided with a 1/4" female thread and accept our combination retriever S 10.



E 16

Gorlitz's installation handle is the ideal tool for on-site installation of all our slip joint cable connectors E 05 thru E 07.



E 24 1/4"
Thread
E 25 3/8"
Thread

Gorlitz's double female connectors are used for quick but temporary cable extensions.



E 30 3/8"
Cable
E 31 1/2"
Cable

Gorlitz's male/female couplers are used for quick cable extensions.

SPLICES



S 01 3/8"
S 02 13/32"
S 03 1/2"
S 04 5/8"
S 05 11/16"
S 06 3/4"


Gorlitz's standard splices are available to repair 3/8" thru 3/4" diameter cables and are unnoticeable once installed.



S 07 5/8"
S 08 11/16"
S 09 3/4"

Gorlitz's hex splices are available to repair 5/8" thru 3/4" diameter cables and are easily recognized once installed.

HOIST



Hoist 02

Gorlitz offers an excellent solution for handling bulky, heavy equipment. The hoist can be mounted inside van or truck beds. This unit, when using the optional sling which is sold separately, can pick up any Gorlitz drain cleaning machine. The hoist has a vertical lifting capacity of up to 1000 lbs., can pivot 360 degrees and have an extended reach capacity of 58".

Base Height 40"
Arm Length 38"
Max Arm Length 58"
Max Arm Height 90"

SPLIT PIN CONNECTORS

Gorlitz's extra long threaded male cable ends E 50 thru E 52 are designed to accept any blade holder E 60 thru E 62 and cone chuck E 63.

E 50	5/8"
E 51	11/16"
E 52	3/4"



Gorlitz's female connectors will lock into any male type fitting securely and are supplied with a split pin. Connectors are available only for 5/8" thru 3/4" diameter cables.

E 53	5/8"
E 54	11/16"
E 55	3/4"



Gorlitz's male connectors will lock into any female type fitting securely. Connectors are available for only 5/8" thru 3/4" diameter cables.

E 56	5/8"
E 57	11/16"
E 58	3/4"



Gorlitz's hexagonal chuck holder accepts blade holders E 60 thru E 62 and cone chuck E 63. The hex shape of the chuck prevents any blade holder from unscrewing.

E 59



Gorlitz's small blade holder is cast in bronze and accepts any 3/4" wide blades K 06 thru K 14. Generally recommended for clearing lines up to 3" in diameter.

E 60



Gorlitz's medium blade holder is cast in bronze and accepts our 3/4" wide blades K 09 and K 12. Generally recommended for clearing 4" in diameter sewer lines.

E 61



Gorlitz's large blade holder is cast in bronze and accepts our 1" wide heavy duty blades K 26 thru K 29. Recommended for clearing lines 3" in diameter and larger.

E 62



Gorlitz's heavy duty 3-blade cone chuck is used on all 3" and larger diameter sewer lines. The outer and inner cones are made of cast bronze. The outer cone has 3 recessed pockets that lock knives in position. This chuck accepts single 3/4" wide knives K 23 thru K 25.

E 63



Gorlitz's split pins are required to lock our male and female split pin connectors.

E 66	1/4" X 5/8"
E 67	1/4" X 3/4"



Gorlitz's specially heat-treated split pin installation handle smoothly guides the split pin through the male and female connectors.

E 68



Gorlitz's male/female split-pin connector can be used to attach leaders to existing cables or it may also be retrofitted as a chuck.

E 74



RETRIEVERS



S 10

Gorlitz's small combination retriever is used to retrieve 3/8", 13/32" and 1/2" diameter cables. One end is an open ended spiral taper with the other being a 1/4" female thread that attaches onto cable ends E 01 thru E 03.



S 11



E 70

Gorlitz's large combination retriever is used to retrieve 5/8", 11,16" and 3/4" diameter cables and may also be used to retrieve rags, diapers and other foreign objects. One end is an open tapered spiral, the other end attaches to a standard cable connector E 05 thru E 07, or female split pin connector E 53 thru E 55.




S 12 5/8"
S 13 11/16"
S 14 3/4"

Gorlitz's hook retrievers are unique pick-up tools that are used to retrieve lost cables. Available in three sizes, they can be attached to a standard cable connector E 05 thru E 07, or female split pin connector E 53 thru E 55.



E 71 5/8"
E 72 11/16"
E 73 3/4"

LEADERS



DHP 01 1/4"
DHP 02 9/32"
DHP 03 5/16"
DHP 04 3/8"
DHP 05 1/2"

Gorlitz's permanent and replaceable downheads help guide the cable thru difficult bends in 1 1/2" to 3" diameter drain lines. Permanent downheads (DHP 01 - DHP 05) are crimped at the factory for proper installation while replaceable downheads (DHR 04 - DHR 05) are attached by threading onto cable ends E 01 thru E 03.



DHR 04 3/8"
DHR 05 1/2"



DHR 06 5/8" to 3/4"

Gorlitz's replaceable downhead assemblies allow the blade to be dropped at any point of cable rotation guiding the cable through difficult turns. They are also quite useful for back to back drains, sudden drops or sharp turns. Downhead DHR 06 is featured with a slip joint end and downhead DHR 07 attaches to a female split pin connector. Recommended for 3" to 6" diameter drain pipes. Blade not included.




DHR 07 5/8" to 3/4"



BHR 01
BHR 02
BHR 03

Gorlitz's replaceable bulbhead BHR 01, plug BHR 02 or as an assembly BHR 03 are available for 13/32" diameter cables. They are quite flexible and used to guide the cable through demanding turns giving the operator the advantage when using blades K 01 thru K 05.



E 17 5/8" X 2'
E 18 11/16" X 2'
E 19 3/4" X 2'
E 64 5/8" X 2'
E 65 3/4" X 2'

Gorlitz's flexible leaders are loosely wound 2' long cable sections that guide sewer cables with ease through difficult turns. The 3/8" diameter male threaded stud accepts different blade holders and cutting blades.




E 22 E 69


Gorlitz's spearhead assembly is recommended to bore through stoppages plugged with grease and/or sand. The cutting blade is hardened and replaceable.

KNIVES & BLADES

Gorlitz's blades K 01 thru K 05 with 1/4" mounting hole are for 3/8", 13/32" and 1/2" diameter cables. They are attached to cable ends E 01 thru E 03. Blade K 03A is made from extra thin material giving it greater flexibility.




Gorlitz's blades K 06 thru K 14 with 3/8" diameter mounting hole are made for 5/8", 11/16" and 3/4" diameter cables. They are used best with our E 20 chuck assembly, or any 3/8" diameter male threaded stud cable end.



Gorlitz's single knives K 19 thru K 22 can only be utilized with cone chucks E 09 and E 09A. Knives K 23 thru K 25 can only be used with 3 bladed cone chuck E 63.



Gorlitz's heavy duty 1" wide blades K 26 thru K 29 with 3/8" diameter mounting hole are made for 5/8", 11/16" and 3/4" diameter cables. They are used best with our E 21 chuck assembly, and our large blade holder E 62. Blade K 16A is an offset blade. One cutting side is 4" the other only 3" long.




Gorlitz's knives and blades are extremely strong and yet are flexible enough for any job! All our knives are die cut and formed when in a soft condition and then heat-treated to our specification. In addition, they are black oxidized and oil dipped to prevent rusting. These hardy blades are offered in many different shapes and sizes depending on the job for which they are needed. Whether you need to cut roots, paper, diapers, napkins, grease, sludge, etc., our knives can even be hand sharpened for a special cutting job. Available with plain or serrated cutting edges, these blades are used with 3/8" up to 3/4" diameter cables to clean sewer lines from 1 1/2" up to 8" in diameter.

ROOTER TOOLS & ACCESSORIES




360-828-5732



T 02

T 02A

Gorlitz's cable feeder mounting bracket is required to install our power cable feeder and pullers. Power feeder bracket T 02 is required for GO 50 thru GO 68HD series machines and T 02A is required for GO 50 series machines.



T 04

T 04A

Gorlitz's loading ramps are designed for simple loading or unloading of our GO 68 (T 04) and GO 62 (T 04A) Series sewer cleaning machines. Our ramps are equipped with a fold down section, wheel stops and mounting hardware. The ramps are painted in black and weigh approximately 57 lbs for model T 04 or 49 lbs for model T 04A. T 04 Overall dimensions with fold down section in upright position are 50" L X 23" W X 20" H. T 04A Dimensions are 42" L X 23" W X 20" H.



T 05

Gorlitz's winch installation kit is provided with a powerful 1500 lbs. full capacity 12 Volt DC motor, a 40 amp 12 Volt fuse, wire harness, forward/reverse switch and manual crank emergency handle.




T 06

Gorlitz's optional pneumatic foot switch is supplied with a standard 6 foot air hose that replaces the electric on/off switch control on our GO 50, GO 62 and GO 68 (series) sewer and drain cleaning models. It allows the operator's hands to be free and provides more flexibility while operating the equipment.



T 07B

Gorlitz's electric foot switch allows the operator's hands to be free to guide the cable while controlling the on/off position of the machine. This unit is made from a heavy duty metal casting and painted in a bright fluorescent color for easy visibility.



T 08

Bulb Head Down Head Down Head
T 10B 3' T 10 3' T 08 3'
T 11B 6' T 11 6'

Gorlitz's toilet augers are available in 3 or 6 foot lengths with bulbhead or downhead attachments. Our auger T 08 comes with 3 foot long flexible hollow core cable specially designed for water-saver toilets, while augers T 10 and T 11 are available only with inner core cables.



T 12

Gorlitz's specially designed 6" diameter ball type extra heavy duty force cup plunger, with a reinforced ribbed construction, is supplied with a 20" long wooded handle. The plumbers choice.



T 13

Gorlitz's hydro-thrust plunger is a large capacity funnel shaped cup that acts as a super-charger against hard to move stop-pages in even oddly shaped toilet bowls. The funnel can be retracted and used in flat sinks and tubs.

ROOTER TOOLS & ACCESSORIES

Gorlitz's tile probes are used to locate buried sewer or drain pipes. Models T 14 and T 15 are made of durable 1/2" diameter solid steel rod. Models T 15B and T 15C are constructed from 1/2" diameter hollow core rod and include a brass hose connection and shut-off valve to control water flow. Probes are powder coated and provided with molded rubber grips for added comfort and are available in different lengths.




T 14 40" T 15B 48"
T 15 48" T 15C 60"

Gorlitz's all purpose gloves are made of a strong, durable canvas. The fingers are composed of a single layer of soft swede leather while the index finger, thumb and palm have a double layer. One size fits all.



T 16

Gorlitz's "ugly" gloves are constructed out of a tough PVC material. The palm is molded with small PVC particles to prevent the operators gloves from twisting or snagging. The gloves themselves are acid and oil resistant, flexible, and keep your hands clean and dry. Available in wrist or forearm length.



T 17 Regular

T 17A Long

Gorlitz's digging bars are helpful tools in aiding the prying or lifting of various cover plates. Constructed out of 7/8" hex material, one side is provided with a chisel shaped end while the other features a sharp point.



T 18 5' T 19 6'

Gorlitz's pressure bags use water pressure supplied from a garden hose to blast open clogged sewer or drain lines. Constructed out of canvas and provided with brass fittings, they are an indispensable item. Available in 5 different sizes.



T 20 1 1/2" T 22 3" T 24 6"
T 21 2" T 23 4"

Gorlitz's vent roller is used to help guide the cable smoothly down the vent pipe and prevents damage to the pipe edge.




T 25

Gorlitz's bolt cutters are used in cutting and repairing broken or damaged cables. Cutting blades are constructed from solid hardened tool steel for extra longevity. Available in 2 sizes.



T 26 24" T 26 30"

Gorlitz's center punch is designed to displace any sharp edges and/or spread the first coil of any cable for easy installation of our cable ends and connectors. Our center punch is heat treated for longer life.



T 27

Gorlitz's splash guards are constructed from nylon reinforced plastic coated canvas. They are recommended for our open reel models to prevent water from splashing onto any nearby surroundings. Models T 28 and T 28S fold together for convenient storage. Models T 28A thru T 28D are provided with rubber bands at each diameter opening for a snug fit on the reel.



T 28A 3/8"
T 28B 1/2"
T 28C 5/8"
T 28D 1 1/16"



T 28
T 28S

RJM**360-828-5732**

MODEL GO 3500

The Model GO 3500 is our largest and most powerful portable jetter. Driven by an 18 HP Honda engine generating up to 3500 psi of cleaning power, it has the capacity to clear the most stubborn blockages.



Gorlitz Model GO 3500, designed to be very compact, offers a one piece frame construction and large capacity hose pay-off reel. Equipped with an 18 HP Honda engine, gear reducer and triplex pump, this unit generates 3500 psi at 5.5 GPM allowing the operator to handle the toughest jobs with ease. Also included is the hydro-pulse feature, which when used can easily blast through tough stoppages clearing sludge, grease, and other residues. Recommended use for the 1/8" trap hose is up to 3" in diameter while the 3/8" hose can handle drain lines from 4" to 10" in diameter over 300 feet long. Gorlitz is offering the Model GO 3500 with a 3/8" rotating nozzle to handle the most demanding applications in the field.

SPECIFICATIONS

18 HP Gasoline Engine
Electric Start / Manual Backup
Triplex Ceramic Plunger Pump
3500 PSI Maximum Working Pressure
5.5 GPM Maximum Water Volume
160° F Maximum Water Temperature
Dimensions: 36"L x 24" W x 46" H
Net Weight: 305 LBS

ACCESSORIES

75' Trap Hose	300' Jetter Hose
Pulsation	Nozzle Assortment
Trigger Gun	Nozzle Cleaning Kit
Wheel Brake	Pop-off Safety Valve
Safety Goggles	Back Flow Check Valve
Mesh Filter	Pressure Regulator
Tool Box	Adjustable Reel Lock
	Gloves

The removable reel has the capacity to store over 300 feet of jetter hose and is fitted with a stainless steel swivel and adjustable reel break. The quick disconnect fittings to pump and reel simplify all hose connections.

This model is our most popular and versatile mid-sized jetter. Available as a standard gas model for typical outdoor use.

Gorlitz Model GO 3000 Series comes standard with electric start and is available with a propane gas conversion. Versatile and functional, this unit is built with a simple design and strong frame construction. Powered by a dependable 13 HP Honda engine and three piston ceramic plunger pump, this model will generate 3000 psi of pressure at 4.5 GPM to clear the most difficult jobs. Model GO 3000 Series, operated with the 1/8" trap hose, can open frozen pipes, clear sludge, grease and soap residues in lines up to 3" in diameter. By simply using the larger 3/8" jetter hose, the same stoppages can be cleared in lines from 4" to 8" in diameter.



ACCESSORIES

75' Trap Hose	Gloves
Pulsation	200' Jetter Hose
Trigger Gun	Pressure Regulator
Hose Guard	Nozzle Assortment
Safety Goggles	Nozzle Cleaning Kit
Mesh Filter	Pop-off Safety Valve
Tool Box	Back Flow Check Valve
	Adjustable Reel Brake

The sturdy 300 foot capacity reel used on this model is identical to our larger Model GO 3500. In addition, the hose guards and mounting rings for our supplied trigger gun are attached directly to the frame. The quick disconnect fittings at the reel, pump and trigger gun are standard equipment and simplify all hose connections.

SPECIFICATIONS

13 HP Gasoline Engine
Electric Start / Manual Backup
Triplex Ceramic Plunger Pump
3000 PSI Maximum Working Pressure
4.5 GPM Maximum Water Volume
160° F Maximum Water Temperature
Dimensions: 31"L x 25" W x 40" H
Net Weight: 185 LBS

MODEL GO 2000

The Model GO 2000 is the choice for those looking for a small powered gas jetter. This unit was designed on the basis of the GO 1500 but incorporating a 6.5 HP Honda engine. Being completely independent of electrical power, it gives the operator complete freedom and mobility.

Gorlitz Model GO 2000 is also well suited with the professional plumbers due to its small size and lighter weight. The triplex ceramic plunger pump, provided with the popular hydro-pulse feature is mounted directly to a 6.5 HP Honda engine. This dependable combination generates up to 2000 psi of cleaning power at 3 GPM and can handle most any cleaning job. Model GO 2000 is supplied with two different size hoses to clear grease, sludge, residues and open frozen pipes from 1 1/2" to 4" in diameter.



SPECIFICATIONS

6.5 HP Gasoline Engine
Manual Start

Triplex Ceramic Plunger Pump
2000 PSI Maximum Working Pressure
3 GPM Maximum Water Volume
160° F Maximum Water Temperature
Hose Reel Capacity:

75' Trap Hose, 150' Jetter Hose
Storage Dimensions: 24" L x 24" W x 29" H
Extended Dimensions: 24" L x 24" W x 43" H
Net Weight: 130 LBS

ACCESSORIES

50' Trap Hose	100' Jetter Hose
Pulsation	Nozzle Assortment
Hose Guard	Nozzle Cleaning Kit
Mesh Filter	Pop-off Safety Valve
Allen Wrench	Back Flow Check Valve
Tool Box	Adjustable Reel Brake
Gloves	Pressure Regulator
	Safety Goggles

Shown with optional spray wand

SHOWN WITH HANDLE DOWN



Our specially designed and divided hose reel accepts two different size hoses for simple storage of the trap hose and for permanent operation of the larger jetter hose. The extendible handle and removable payoff reel are provided with quick disconnect hardware for easy break down and loading of the jetter. Quick disconnect fittings to hoses, reel and pump are included.

MODEL GO 1500

This electric jetter is the alternative choice to our gas powered models. Simply built, this unit will perform well with limited maintenance and care.

Gorlitz Model GO1500 was designed with portability in mind. The frame is constructed with a retractable handle, which locks in the up and down position for easy transportation or storage. Equipped with a custom built dual capacitor 2 HP motor, this jetter will draw 19.8 amps at full load. The duplex ceramic plunger pump equipped with pulsation will generate over 1500 psi at 2.1 GPM. This model is supplied with two hose sizes on a removable split reel, giving the operator the capability to clear sludge, grease, residues and open frozen lines from 1 1/2" to 4" in diameter.

ACCESSORIES

50' Trap Hose	100' Jetter Hose
Pulsation	Nozzle Assortment
Hose Guard	Nozzle Cleaning Kit
Mesh Filter	Pressure Regulator
Allen Wrench	Adjustable Reel Brake
Tool Box	Hose Shutoff Valve
Gloves	25' Cord with GFCI
	Safety Goggles

SHOWN WITH HANDLE DOWN



SPECIFICATIONS

2 HP (19.8 AMPS) Motor
Duplex Ceramic Plunger Pump
1500 PSI Maximum Working Pressure
2.1 GPM Maximum Water Volume
180° F Maximum Water Temperature
Hose Reel Capacity:
75' Trap Hose, 150' Jetter Hose
Storage Dim: 20" L x 24" W x 27" H
Extended Dim: 20" L x 24" W x 41" H
Net Weight: 129 LBS

The frame and reel design of this model is a mirror image of our slightly larger model GO 2000. In addition, the frame has been outfitted for convenient extension cord storage while the electrical control box provides additional outlets.



360-828-5732

MODEL GO 1500A

Well built and packed with power, Gorlitz Model GO 1500A is the most compact and powerful jetter in its class. Our specially designed motor and dual pulsation make it the most desired small jetter in the industry.



Gorlitz Model GO 1500A is well recognized due to its smaller size, simplicity and portability. The functional frame construction is provided with a pullout handle and wheels for easy transportation to the job site. This model is also equipped with our 2 HP motor and duplex ceramic plunger pump to generate a working pressure of over 1500 psi. In the pulsation mode, Model GO 1500A will open the most stubborn drain lines from 1 1/2" to 3" in diameter.

SHOWN WITH OPTIONAL HOSE REEL #1535

SPECIFICATIONS

2 HP (19.8 AMPS) Motor
Duplex Ceramic Plunger Pump
1500 PSI Maximum Working Pressure
2.1 GPM Maximum Water Volume
180° F Maximum Water Temperature
Storage Dimensions: 22" L x 15" W x 14" H
Extended Dimensions: 38" L x 15" W x 14" H
Net Weight: 74 LBS

ACCESSORIES

50' Trap Hose	Pressure Regulator
Pulsation	Hose Shutoff Valve
Mesh Filter	Nozzle Assortment
Allen Wrench	Nozzle Cleaning Kit
Safety Goggles	25' Cord with GFCI
Gloves	

This "Little Jetter" is of exceptional design and is provided with pulsation, quick disconnect hose fittings, 50 feet of trap hose and a complimentary set of three jetter nozzles.




360-828-5732

HOSE CADDY

Gorlitz portable hose caddy or dolly allows the operator to take the unit inside a building while the jetter stays outside. They can also be used to extend the reach of any jetter.

Gorlitz portable hose caddy is provided with a divided reel to store two different size hoses if needed. Maximum hose capacities are 100 feet of trap hose and 150 feet of 1/4" small jetter hose. Caddy includes protective rubber feet, swivel, shutoff valve and quick disconnect fitting. Maximum working pressure is 2000 psi. Weight: 35 lbs. (without hoses)



JT 109

CADDY PICTURED WITH OPTIONAL HOSES

HOSE DOLLY

Gorlitz hose dolly is equipped with a large capacity reel capable of storing over 300 feet of 3/8" jetter hose. The reel is fitted with one quick disconnect fitting, stainless steel swivel and shutoff valve, pressure gauge and adjustable reel brake.

The low profile frame is designed with an extendible handle to lock in the upright position for transportation and lowers to reduce storage space. Dolly is provided with pneumatic tires and protective rubber feet. Maximum working pressure is 4000 psi.

Weight: 75 lbs. (without hose)



JT 110

Page 27

JETTER HOSES

Gorlitz's jetting hoses are recognized for their abrasive resistant cover, smooth bore, chemical resistance and non-metallic properties. Most important, they are lightweight and offer great flexibility when under pressure.

Gorlitz's 1/8" diameter trap hose is recommended for 1 1/2" to 3" diameter drains. Both ends are equipped with rigid pipe thread fittings.



Gorlitz's small 1/4" diameter jetter hose is provided with one rigid and one swivel pipe thread fitting. Suggested applications are from 2" to 4" diameter pipes.



Gorlitz's medium 3/8" diameter jetter hose is recommended to clear lines from 4" to 8" diameter. Includes one rigid and one swivel pipe thread fitting.



Gorlitz's large 1/2" diameter jetter hose will clear main lines from 4" in diameter. Each hose includes one swivel and one rigid pipe thread fitting.



All Gorlitz jetter hoses are listed by their inside diameters and are equipped with standard National Pipe Thread fittings. They are also available in different lengths upon requests.

ROTATING NOZZLES

Gorlitz's rotating nozzles are recommended for their superior cleaning power. Applications include the cutting of grease, sludge, residues and the de-scaling of pipes. Larger models are available with a single forward jet which will assist in the breakup of frontal blockages. Made from stainless steel and heat treated for durability and longer life.

Models JN 10A, JN 20A, JN 30A and JN 40A are available with 4 rear jets and a single forward jet.

Gorlitz's flexible leaders help rotating nozzles negotiate difficult turns. Replacement leader JN 29A is recommended for model JN 30 FL. Replacement leader JN 39A is used with model JN 40 FL.

Nozzles machined with a 1/8" and 1/4" national pipe thread should not exceed 3000 psi. Nozzles provided with 3/8" and 1/2" national pipe thread should not exceed 4000 psi of working pressure.

JN 10 1/8" 2-3 GPM
JN 20 1/4" 2-4 GPM
JN 30 3/8" 4-6 GPM
JN 40 1/2" 8-10 GPM



JN 10A 1/8" 2-4 GPM
JN 20A 1/4" 2-4 GPM
JN 30A 3/8" 4-6 GPM
JN 40A 1/2" 8-10 GPM



4 Rear Jets with
one Forward Jet



4 Rear Jets with
Flexible Leader

JN 30 FL 3/8" 4-6 GPM
JN 40 FL 1/2" 8-10 GPM

JETTER NOZZLES

Gorlitz's standard nozzles, available in brass or stainless steel, are recognized for their precision machining and short overall length to accomplish tight turns. Precise jets and smooth orifices offer rapid forward movement and superior cleaning power.



Thrust Nozzle
3 Rear Jets

JN 01	1/8" 2-3 GPM	JN 01B	1/8" 2-3 GPM
JN 11	1/4" 2-4 GPM	JN 11B	1/4" 2-4 GPM
JN 21	3/8" 4-6 GPM		



Thrust Nozzle
4 Rear Jets

JN 22	3/8" 4-6 GPM
JN 32	1/2" 8-10 GPM



Thrust Nozzle
6 Rear Jets

JN 03	1/8" 2-3 GPM	JN 03B	1/8" 2-3 GPM
JN 13	1/4" 2-4 GPM	JN 13B	1/4" 2-4 GPM
JN 23	3/8" 4-6 GPM		
JN 33	1/2" 8-10 GPM		

Gorlitz's thrust head nozzles are equipped only with rear jets for maximum forward propulsion. Suggested for general applications.



Laser Nozzle
3 Rear Jets

JN 04	3/8" 4-6 GPM	JN 04B	1/8" 2-3 GPM
JN 14	3/8" 4-6 GPM	JN 14B	1/4" 2-4 GPM
JN 24	3/8" 4-6 GPM		



Laser Nozzle
4 Rear Jets

JN 25	3/8" 4-6 GPM
JN 35	1/2" 8-10 GPM

Gorlitz's laser tip nozzles are manufactured with three or more rear jets and one jet pointing forward to help cut through ice, sludge, grease, etc.



Laser Nozzle
6 Rear Jets


JN 06	1/8" 2-3 GPM	JN 06B	1/8" 2-3 GPM
JN 16	1/4" 2-4 GPM	JN 16B	1/4" 2-4 GPM
JN 26	3/8" 4-6 GPM		
JN 36	1/2" 8-10 GPM		



Corner Nozzle
2 Rear Jets

JN 07	1/8" 2-3 GPM	JN 07B	1/8" 2-3 GPM
JN 17	1/4" 2-4 GPM	JN 17B	1/4" 2-4 GPM

Gorlitz's corner head nozzles are provided with two rear jets for propulsion and one side jet to assist in making difficult turns.



Drop Head
Nozzle
3 Rear Jets

JN 08	1/8" 2-3 GPM	JN 08B	1/8" 2-3 GPM
JN 18	1/4" 2-4 GPM	JN 18B	1/4" 2-4 GPM

Gorlitz's drop head nozzles are highly recommended to negotiate back to back drains or sharp turns.



Drop Head
Nozzle
6 Rear Jets

JN 09	1/8" 2-3 GPM	JN 09B	1/8" 2-3 GPM
JN 19	1/4" 2-4 GPM	JN 19B	1/4" 2-4 GPM

Gorlitz's flex corner nozzles were designed for 3/8" and larger diameter jetting hoses. The flexible 8" long spring section including bulb is replaceable. Suggested applications include difficult turns or sharp bends.



Flex Corner
Nozzle
4 Rear Jets

JN 29	3/8" 4-6 GPM
JN 39	1/2" 8-10 GPM

Note: Nozzles made from brass (identified by the letter "B") should not exceed 2000 psi. Nozzles made from stainless steel should not exceed 4000 psi of working pressure unless specified otherwise. Specialty nozzles are available. Please inquire.




Flex
Replacement
Tip

JN 29A	3/8"
JN 39A	1/2"

BALL NOZZLES

Gorlitz's ball shaped nozzles are an alternative to our drop head nozzles. The oversized ball (1.0" Diameter) shape gives added weight to clean the bottom of the pipe, negotiate bends, turns and back to back drains. Available in brass only.



Gorlitz's ball head nozzles JB 01 and JB 03 are machined with three or six rear jets for maximum forward propulsion. JB 04 and JB 06 laser tip ball nozzles are machined with three or six rear jets and one jet pointing forward.

JB 01 1/8" 2-3 GPM (3)
JB 03 1/8" 2-3 GPM (6)
JB 04 1/8" 2-3 GPM (3/1)
JB 06 1/8" 2-3 GPM (6/1)

JETTER TOOLS & ACCESSORIES

Gorlitz's adjustable in-line liquid injectors are made from brass and stainless steel components. Injectors are provided with 3/8" quick disconnect fittings and 1/4" hose barb. Maximum operating temperature is 180° F and 3000 psi of pressure.



JT 101 3-5 GPM

Gorlitz's liquid strainer assembly includes 8 feet of 1/4" diameter clear hose. The strainer is made from high impact reinforced nylon and supplied with 1/8" to 1/4" hose barb.



JT 102

Gorlitz's 4000 psi heavy duty trigger gun assembly includes a 36" lance with molded grip. The spray tip incorporates an adjustable high/low variable fan nozzle. The handle is contoured to provide comfort, safety and smooth trigger action. Fittings are 3/8" NPT inlet and 1/4" outlet.



JT 103

Gorlitz's constant speed turbo nozzle will produce up to 3500 psi of cleaning power. Applications include removal of paint, rust, scale, algae and graffiti.



JT 104

Gorlitz's super flexible premium grade PVC gloves offer an excellent wet/dry grip and are also used to handle acids and caustics. They are abrasion resistant and suited best to handle oily, greasy materials. Treated with antibacterial agents actifresh.



JT 105

Gorlitz's nozzle cleaning kit contains an assortment of specially designed and tempered wire files to clean most any nozzle orifices.



JT 106

Gorlitz's low pressure garden hose shutoff valve simplifies the water on/off procedure. Provided with standard 3/4" garden hose fitting.



JT 107

MODEL COMPARISON CHART

SEWER & DRAIN CLEANING MACHINES

MODEL	CABLE SIZE	MOTOR	CABLE RPM	PIPE DIAMETER	APPLICATION
GO 15	1/4" X 35'	1/6 HP CAPACITOR	265	1 1/4" TO 2"	TUBS SINKS SHOWERS
GO 250	1/4" X 50'	1/4 HP CAPACITOR	230	1 1/4" TO 2"	TUBS SINKS SHOWERS
GO 31	5/16" X 25'	1.85 AMP	0-450	1 1/4" TO 2"	TUBS SINKS SHOWERS
GO 380	3/8" X 65'	1/4 HP CAPACITOR	230	1 1/2" TO 3"	VENTS SMALL DRAINS
GO 380A	3/8" X 90'	1/4 HP CAPACITOR	230	1 1/2" TO 3"	VENTS SMALL DRAINS
GO 380/250	3/8" X 65' 1/4" X 50'	1/4 HP CAPACITOR	230	1 1/4" TO 3"	TUBS, SINKS SHOWERS SMALL DRAINS
GO 380A/250	3/8" X 90' 1/4" X 50'	1/4 HP CAPACITOR	230	1 1/4" TO 3"	TUBS, SINKS SHOWERS SMALL DRAINS
<u>GO 50</u> GO 50 PE	1/2" X 80'	1/3 HP CAPACITOR	190	2" TO 3"	VENTS SMALL DRAINS LIGHT ROOTS
<u>GO 50A</u> GO 50A PE	3/8" X 90'	1/3 HP CAPACITOR	190	1 1/2" TO 3"	VENTS SMALL DRAINS
<u>GO 50B</u> GO 50B PE	13/32" X 75'	1/3 HP CAPACITOR	190	2" TO 3"	VENTS SMALL DRAINS LIGHT ROOTS
<u>GO 62</u> GO 62 PE	3/8" X 90' 1/2" X 80' 5/8" X 100'	1/4 HP GEARED	165	1 1/2" TO 4"	VENTS DRAINS MEDIUM ROOTS
<u>GO 62A</u> GO 62A PE	5/8" X 100'	1/4 HP GEARED	165	3" TO 4"	VENTS DRAINS MEDIUM ROOTS
<u>GO 68</u> GO 68 PE	11/16" X 150'	1/2 HP GEARED	160	3" TO 8"	DRAINS ROOTS SAND, GREASE
<u>GO 68 HD</u> GO 68 HD PE	11/16" X 150'	3/4 HP CAPACITOR GEAR BOX	175	3" TO 10"	DRAINS ROOTS SAND, GREASE

MODEL COMPARISON CHART (CONT)



360-828-5732

SEWER & DRAIN CLEANING MACHINES (CONT)

OVERALL DIMENSION	NET WEIGHT	SHIPPING WEIGHT	BLADES	CONE CHUCK	REG. CHUCKS	CONNECTORS	ENDS	SPLICES	RETRIEVERS	WRENCHES	TOOL BOX	FOOT SWITCH	CABLE FEEDER
16" L 10" W 14" H	28	32								2	OPT	OPT	
18" L 14" W 16" H	39	44								3	OPT	OPT	
17" L 9" W 9" H	13	15									OPT		
18" L 14" W 16" H	49	54	5				2	2	OPT	3	OPT	OPT	
18" L 14" W 16" H	55	60	5				2	2	OPT	3	OPT	OPT	
18" L 14" W 16" H	65	75	5				2	2	OPT	3	OPT	OPT	
18" L 14" W 16" H	71	81	5				2	2	OPT	3	OPT	OPT	
28" L 18" W 19" H	<u>90</u> 86	<u>100</u> 96	5				2	2	OPT	2	OPT	OPT	OPT
28" L 18" W 19" H	<u>76</u> 71	<u>86</u> 81	5				2	2	OPT	2	OPT	OPT	OPT
28" L 18" W 19" H	<u>76</u> 71	<u>86</u> 81	5				2	2	OPT	2	OPT	OPT	OPT
35" L 22" W 24" H	<u>228</u> 216	<u>258</u> 246	12	OPT	2	2	4	6	1	2	1	1	OPT
35" L 22" W 24" H	<u>153</u> 146	<u>183</u> 176	5	OPT	2	2	OPT	2	1	2	1	1	OPT
43" L 26" W 30" H	<u>238</u> 231	<u>268</u> 261	12	1	2	2	OPT	2	1	2	1	1	OPT
43" L 26" W 30" H	<u>255</u> 248	<u>285</u> 278	12	1	2	2	OPT	2	1	2	1	1	OPT



HIGH PRESSURE WATER JETTERS

NOTES

TERMS & CONDITIONS

HOW TO ORDER

In order to avoid mistakes or delays of your shipment, please refer to our part number and description.

PRICES

Since prices are subject to change we cannot guarantee them for more than 30 days. The prices listed are valid for the period indicated on the cover of the price list only. Prices are Net F.O.B. Factory, Santa Fe Springs, California.

SALES TAX

Gorlitz Sewer & Drain, Inc. is required to charge applicable State Sales Tax on every item sold unless a California State Sales Tax Exemption Certificate has been provided.

FREIGHT POLICY

All merchandise shipped per parcel service are prepaid and added to the invoice. All shipping fees per trucking lines are the responsibility of the customer. If any freight damages or losses are experienced, Gorlitz Sewer & Drain, Inc. requests that the freight company carrying the merchandise be contacted by the customer for freight claims.

MERCHANDISE CLAIMS AND RETURN POLICY

All discrepancies in goods received must be claimed within five days after receipt of goods. Any item to be returned must be referenced by invoice number, date of sale and written consent of seller.

GORLITZ LIMITED WARRANTY

All products manufactured at Gorlitz Sewer & Drain, Inc. are warranted to be free from defects in material and workmanship under normal use and maintenance for a period of one (1) year from date of purchase to original buyer. If any parts break or fail, we ask you to notify your nearest dealer or Gorlitz Sewer & Drain, Inc. and supply us with proof of purchase and nature of failure. Gorlitz will repair or replace (at our option) any parts found to be defective. The replacement part assumes the unused portion of the warranty. Transportation of the product to any service station is the responsibility of the user unless stated otherwise in this warranty.

This warranty does not apply to expendable items (Cables, Knives, Nozzles, Hoses, Fittings, etc.) and damage due to negligence, unauthorized repair or alteration, chemicals, misuse or accidents. Adjustments of any kind can not be made on shaved, kinked or broken hoses and kinked or broken cables because it shows evidence of abuse or to much pressure.

This warranty is exclusive and in lieu of all other expressed warranties and Gorlitz Sewer & Drain, Inc. does not authorize any part to assume for it any other obligation or liability. In no event shall Gorlitz Sewer & Drain, Inc. be liable for special or consequential damages arising from the use of this product or for any delay in the performance of this warranty due to causes beyond our control.

In placing this order Buyer expressly understands, acknowledges and agrees that: (1) Buyer has received and read the Operating and Maintenance Instructions that accompanied this equipment order, including Gorlitz's Limited Warranty and all of the other Terms and Conditions of doing business with Gorlitz Sewer & Drain, Inc. ("Gorlitz") as stated therein; (2) Buyer will operate and maintain the equipment in accordance with the specifications stated in the Instructions; (3) Buyer indemnifies and holds Gorlitz harmless for Buyer's failure to use the equipment in accordance with the specifications stated in the Instructions; (4) the equipment is being sold to Buyer on an "as is" and "where is" basis and that except as specifically set forth in this agreement, Gorlitz makes no other representations or warranties, whether express or implied; and (5) all disputes arising under this agreement shall be submitted to courts of competent jurisdiction in the State of California and the prevailing party in any action or proceeding to enforce any provision of this agreement will be awarded reasonable attorney fees and costs incurred in that action or proceeding or in efforts to negotiate the matter.

MANUFACTURERS WARRANTIES AND LITERATURE

Most products used on our equipment are warranted to the final consumer by their manufacturers. Copies of such warranties are supplied with our products or are available from the manufacturers. As a service, Gorlitz Sewer & Drain, Inc. will obtain copies of consumer warranties from the warrantor and will furnish them free of charge to consumers upon request. Gorlitz Sewer & Drain, Inc. assumes no responsibility for the content of such warranties or sales literature by performing this service.

Due to a continuing program of product improvement, Gorlitz Sewer & Drain, Inc. reserves the right without obligation to revise prices, specifications and equipment.