

HATHORN® H2

CAMERA SYSTEM

PROUDLY DESIGNED AND MANUFACTURED IN NORTH AMERICA



Industry
Leading
Warranty



Compatible with
18V Milwaukee®
or Equivalent Batteries



100 ft. - 200 ft.
of Push Rod



512Hz High
Power Sonde



Self-Leveling
Camera Heads

Hathorn® M2 systems come standard with a 7" shatter resistant LCD monitor, 100ft. or 200ft. of premium push rod and your choice of straight-view or self-leveling DuraCAM camera heads, all with cool running super bright LED lights. New for 2023 Hathorn® has added an on-screen footage counter in feet and meters, as well as 512Hz high power sonde control.

Being aimed at the budget conscious user who wants a robust, easy to use system, without paying for extra options, the M2 camera system does not have a recording option. The M2 is an entry level inspection camera offering the same municipal grade quality and portability of our more expensive models. All Hathorn® products are compatible with 18V Milwaukee® batteries offering the M2 over 5 hours of runtime on a single charge.

Trusted by plumbers and contractors to deliver rugged dependability and portability. Designed and manufactured in North America, with a full one-year warranty.



HATHORN®
INSPECTION CAMERAS



RJM Equipment Sales, Inc
800-620-4773
www.rjmcompany.com
sales@rjmcompany.com

HATHORN[®] H2

CAMERA SYSTEM

PROUDLY DESIGNED AND MANUFACTURED IN NORTH AMERICA



Specifications

Display

Size & Type	7" (17.8cm) impact resistant LCD
Resolution & Brightness	1024 x 600 pixels with 500 cd/m2

Features

Footage Counter	Feet or meters with reset function
Sonde Frequency	High power 512Hz
Push Rod	HPDE push rod with coax core

Power

Battery	Only Milwaukee [®] M18 18V or equivalent (not included)
Battery Life	~5-6hrs using 3.0Ah (when not recording & sonde off)
AC/DC Adapter	12V - 4.1A (included)

Weight & Dimensions

Weight without Battery	45lb (20Kg)
Dimensions (L x W x H)	33" x 19" x 16" (84cm x 48cm x 41cm)

Environmental

Water Resistance	IP65 when lid closed / IP64 when lid open
Operating Temperature	14°F to 122°F (-10°C to 50°C)
Storage Temperature	-4°F to 140°F (-20°C to 60°C)

Catalog #	Camera Head	Self Leveling	Rod Length	Rod Size	Min. 90 Elbow	Max. Pipe Well Lit
H2-2168-SL	1.68"	Yes	200 ft.*	1/2"	3"	12"
H2-2168	1.68"	No	200 ft.*	1/2"	3"	12"
H2-2143-SL	1.43"	Yes	200 ft.*	1/2"	3"	10"
H2-2143	1.43"	No	200 ft.*	0.400"	3"	10"
H2-2123-SL	1.23"	Yes	200 ft.*	3/8"	2"	6"
H2-2123	1.23"	No	200 ft.*	3/8"	2"	6"
H2-2100	1.00"	No	200 ft.*	1/4"	1.5"	4"

*100 ft. Lengths of Push Rod Available.



RJM Equipment Sales, Inc
800-620-4773
www.rjmcompany.com
sales@rjmcompany.com