



Industry Leading Warranty



Screen Shot Function

Compatible with

18V Milwaukee®



Internal Hard Drive 64GB or 128GB



Record to USB & HDD

200 ft. of



Push Rod as Standard



Self-Leveling Camera Heads









or Equivalent Batteries

product that is aimed at the residential plumbing, contracting and home inspection markets. This all-in-one system comes equipped with your choice of 200ft. of premium cable and Hathorn DuraCAM camera heads, all with cool running super bright LED lights.

The H7 leads the industry with its impact resistant 7" LCD screen having twice the brightness of comparable inspection cameras in its class. It will operate in any light condition, including direct sunshine, providing stunning picture quality revealing details missed by other lateral push cameras.

The H7 allows the user to save videos and screen shots to the internal hard drive or USB, operate in three menu languages and extend your 18V external battery runtime with the built-in Hathorn® battery extender feature. It will even automatically save your videos before powering down due to a low battery. Never lose another inspection video again!

Trusted by plumbers, home inspectors and contractors all over North America to deliver rugged dependability and portability. Designed and manufactured in North America, with a full one-year warranty. Whether you are working in brutal Canadian winters or hot Arizona summers, inside or outside, a new standard for features and quality has been set with the Hathorn® H7.

<u>^HATHORN" OJM</u> INSPECTION CAMERAS

RJM Equipment Sales, Inc 800-620-4773 www.rjmcompany.com sales@rjmcompany.com

HATHORN H7

CAMERA SYSTEM

Specifications

Display

Size & Type 7" (17.8cm) impact resistant daylight readable LCD Resolution & Brightness 1024 x 600 pixels with 1,000 cd/m2

Recording, Storage & Features

Recording Options	MPEG4 video (H.264 at 30fps) and JPEG screenshot
Storage Options	USB, HDD or USB & HDD
USB Capacity	USB 2.0 up to 32Gb
Hard Drive Capacity	64Gb SSD (standard) or 128Gb SSD (upgrade)
Menu Languages	English, Spanish, French
Footage Counter	Feet or meters with reset function
Sonde Frequency	High power 512Hz
Push Rod	200ft. of HPDE push rod with coax core

Power

Battery	Only Milwaukee® M1818V or equivalent (not incl.)
Battery Life	~5-6hrs using 3.0Ah (when not recording & sonde off)
Battery Extender	Auto dimming & auto saving
AC/DC Adapter	12V - 4.1A (included)

Weight & Dimensions


Weight without Battery 451b (20Kg) Dimensions (Lx Wx H) 33" x 19" x 16" (84cm x 48cm x 41cm)

Environmental

Water Resistance	IP65 when lid closed / IP64 when lid open
Operating Temperature	14°F to 122F (-10C to 50°C)
Storage Temperature	-4°Fto 140°F (-20°C to 60°C)

<u>^HATHORN DJ/</u>

INSPECTION CAMERAS "





RJM Equipment Sales, Inc 800-620-4773 www.rjmcompany.com sales@rjmcompany.com

PROUDLY DESIGNED AND MANUFACTURED IN NORTH AMERICA

ATHOR